

# MSD585 Suspenders (MA7650) Attachment Instructions

3870 Mustang Way  
Bellingham, WA  
USA 98226

TOLL FREE  
EMAIL  
WEB

1.800.526.0532  
mustangusa@mustangsurvival.com  
www.mustangsurvival.com



Suspenders are not required when using the MSD585, unless sizing dictates. However, properly attached suspenders may improve the fit and mobility. The MSD585 is not shipped with the suspenders, but is equipped with attachment loops that accommodate the suspender system. Remove and re-attach as required.

**Required materials:** MSD585 AS or LS and two suspenders (optional accessory not supplied with the MSD585).

## Suspender Attachment Instructions

**Step 1** - Completely unzip the MSD585 entry zipper (as shown below).



**Step 2** - Open the suit so that the (front and back) attachment loops are accessible (as shown below).



**Step 3** - Attach the end of the suspender, with the buckle, to the suit's front attachment point by unpeeling the Velcro flaps and lifting the Velcro strap that is folded on itself. Fold the flaps over the strap (so that hook Velcro faces hook Velcro). Pass the suspender through the attachment loop. The strap end can now be folded over itself so the the Velcro patches close. To secure the suspender, wrap the Velcro flaps around the edges of the strap and attach to Velcro on the opposite side of the strap.



**Step 4** - While keeping the strap straight, attach the non-adjusting end of a suspender to the suit's back attachment point (as shown below). This procedure should be similar to Step 3.



**Step 5** - Repeat these steps to attach the other suspender. It is recommended to use two suspenders for even support.

**Step 6** - Alternatively, the suspenders may be attached so they are crossed over the user's back.

**Step 7** - Use the suspender strap ends to adjust for a secure comfortable fit.

